




T3H, T3P IO-Link

T-Series III **Data Sheet**



- + Updated new generation: stronger performance
- + Direct analog output, position and speed
- + Full scale adjustable, 100% adjustable zero and full scale
- + IO-Link signal output



THE NEW GENERATION



Double anti-interference



High performance chip




Reverse polarity protection



Shock/vibration resistant

Input	Measured data	Position/Speed				
	Position measurement range	T3H	25mm...7650mm			
		T3P	25mm...5600mm			
	Speed measurement range	0.01...10m/s				
Output	Interface	IO-Link 1.1				
	Data format	32-bit signed				
	Process data Master – Device	0 Byte				
	Transmission rate	Rate(bit/s) Port	4800 COM1	38400 COM2	230400 COM3*	
Resolution	Position resolution	1/2/5*/10/20/50/100μm				
	None-Linearity	< ±0.01%F.S. (min. ±20μm)				
	Repeatability	< ±0.002%F.S. (min. ±5μm)				
	Update time	Stroke length	≤ 1200mm	≤ 2400mm	≤ 4800mm	≤ 7650mm
		Update time	0.5ms	1ms	2ms	5ms
Temperature coefficient	<30ppm/°C					
Mounting	Mounting position	Any				
	T3P aluminum profile	Removable fixing card				
	T3H pressure resistant outer tube	Threaded: metric M18x1.5, metric M20x1.5, metric M24x1, 3/4"-16UNF-3A				
Design/ Material	T3H	Electronics housing: aluminum alloy/zinc alloy Measuring rod: stainless steel 304/316L Magnet: standard magnet/open magnet				
	T3P	Electronics housing: aluminum alloy/zinc alloy Profile: aluminum alloy Magnet: slider magnet/suspension magnet/U-magnet/U-magnet				
	Operating pressure	35MPa (continuous) ,70MPa (peak)				
Electrical connection	Wiring connection	5 pin M12 connector				
	Operating voltage	+24VDC (-15/+20%)				
	Polarity protection	Up to -36VDC				
	Overvoltage protection	Up to +36VDC				
	Power consumption	< 40mA (varies with range size)				
	Dielectric strength	500 VDC (DC ground to machine ground)				
Operating conditions	Magnet speed	Slider magnet ≤ 10m/s; magnetic ring, any; suspension magnet, any.				
	Operating temperature	-40...85°C				
	Humidity	90 % relative humidity, no condensation				
	Ingress protection	IP67				
	Shock	150 g/11 ms, IEC standard 60068-2-27				
	Vibration	30 g/10...2000 Hz, IEC standard 60068-2-6 (resonant frequencies excluded)				
	EMC	Electromagnetic emission according to EN 61000-6-3 Electromagnetic immunity according to EN 61000-6-2				
ITEM	CATEGORY	PARAMETER				

“*” as default




FUNCTION

5 pin M12 connector	D512	PIN	Function
	<p>View on sensor</p>	1	+24VDC (-15/+20%)
		2	-
		3	GND
		4	C/Q(communication line)
		5	-

Enhanced monitoring and diagnostic functions

TECHNOLOGY PERCEIVES THE FUTURE



Green light	Function	Red light	Function
FLASH	Normal communication	OFF	Magnet within effective range
OFF	Communication exception	ON	Magnet leaves effective range or magnet cannot be detected

The built-in LED indicator light provides basic fault feedback and fault alarm of the sensor.

ORDER CODE

T3H - - - - **M**- - - - **L** - - - -

Thread	Stroke length	Connection type	Output
M Metric M18x1.5	0025...7650mm (5mm increments)	D512 5 pin M12 connector	(Output Code)
V Metric M20x1.5			
S 3/4"-16UNF-3A			
W Metric M24x1			
R Metric M18x1.5, with M4x6 thread at tail end			

T3P - - - - **M**- - - - **L** - - - -

Magnet	Stroke length	Connection type	Output
S Magnet slider joint at top	0025...5600mm (5mm increments)	Same as above	(Output Code)
V Magnet slider joint at front			
F Suspension magnet			
U U-magnet			

IO-Link Output Code	L [1][2][3]-[4]			
L Interface	[1] Resolution	[2] Output	[3] IO-Link version	[4] Magnet number
L IO-Link	1 5µm*	1 Position	1 V1.1, COM 1	1 one magnet *
	2 2µm	2 Position and speed*	2 V1.1, COM 2	2 two magnets
	3 10µm	3 2 positions	3 V1.1, COM 3*	3 three magnets
	4 50µm	4 2 positions and 2 speeds		
	5 100µm	5 Configurable outputs		
	7 20µm			
	8 1µm			

“*” as default


Model selection | Model: T3H-M-0600M-D512-L123-1

Explanation: T series III generation, T3H pressure resistance outer tube type, mounting thread metric M18x1.5, stroke length 600mm, 5 pin M12 connector, IO-Link output ,resolution 5µm ,position and speed measurement, V1.1,COM3,single magnet.

■ Please contact us for more customized products.


PARTS SELECTION

TECHNOLOGY PERCEIVES THE FUTURE





Name	Ring magnet	Ring magnet	U-magnet	Ring magnet
Operating temperature	-40...125°C			
Order code	12-1032	12-1019	12-1017	12-1001



Fitting non-magnetic gasket




Name	Non-magnetic gasket	Non-magnetic gasket	Non-magnetic gasket	Non-magnetic gasket
Operating temperature	-40...125°C			
Order code	12-1037	12-1021	12-1018	12-1008




Name	Magnet slider S, joint at top	Magnet slider V, joint at front
Operating temperature	-40...105°C	
Order code	12-1114	12-1115



Name	Suspension magnet 31x20	Suspension magnet 38x25
Operating temperature	-40...105°C	
Order code	12-1010	12-1009



Width: 15mm



Width: 15mm

Name	Removable fixing card	Removable fixing card
Order code	11-1003	11-1004



Connector	5 pin M12 female connector	5 pin M12 female connector (90 degree angle)
Name	Integral cable	Integral cable
Cable	5 wire 0.25mm ² shielded cable	5 wire 0.25mm ² shielded cable
Color/Diameter	Orange/ Ø 6	Orange/ Ø 6
Plug surface	 <ul style="list-style-type: none"> 1-Brown 2-Green 3-White 4-Gray 5-Yellow 	 <ul style="list-style-type: none"> 1-Brown 2-Green 3-White 4-Gray 5-Yellow
Length	5...30M	5/10/15/20/30M
Order code	16-1035	16-1040

Building 6, Dazu Enterprise Bay,
8th yard of Liangshuihe 2nd street, BDA P.R.China

Tel: +86 10-67948976 67948916
Fax: +86 10-67948979
Technical support: +86 (0)13370126657

Beijing Tebeifu Electronic Technology Co., Ltd.

www.tbfsensor.com

